



Illustrative picture

SPECIFICS

<i>Description</i>	Product type	ACS panel IP65 with 4 sockets series 11 IP67
	Article code	2240E
	Commercial Series	ACS PANELS FOR BUILDING SITES IP 65

General Data	Poles	N°	2P+T	Type of material	Abs / Nylon					
	Current	A	16	Dimensional stability	°C -25 +80					
	Voltage	V~	200-250	Resistance glow wire test	°C 650 - 850					
	Power	kW	3	Working temperature	°C -,25 + 40					
	Degree of protection	IP	65	Weight	kg 2,8					
	Impact Resistance	IK	8	Portable	Yes					
	Insulation Resistance	MΩ	>10	Emergency push button	No					
	Dimensions LxDxH	cm	17x21,5x36,5	Connection	Plug					
	Behaviour with chemical and atmospheric agents									
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Limited Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Resistant 

<i>Standards</i>	CEI EN 61439-1	CEI EN 61439-4	2014/35/UE
------------------	----------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	2,8
	Package innerbox		1	2,82
	Packaging			

<i>Description</i>	Composition of the ACS Panel			
	1 Movable plug 16A 2P+T 6h/ IP 67 200-250 V~ 50/60 Hz			
	4 Sockets 16A 2P+E 6h/ IP67 200-250 V~ 50/60 Hz			
	DF 25A 2P 0,03A A			
	MT 16A 2P 6KA			



CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015

Reg. A.E.E n° IT17100000010057

Rev	Date	Technical Manager
01	7/1/20	Romano Rosi